

## SKPT

Version 3.0      Revision Date: 12/04/2017      SDS Number: 290166-00005      Date of last issue: 10/24/2016  
Date of first issue: 10/07/2015

---

**SECTION 1. IDENTIFICATION**

Product name : SKPT

**Manufacturer or supplier's details**

Company name of supplier : Shikoku Chemicals Corporation  
Address : 8-537-1, Doki-cho Higashi  
Marugame-shi, Kagawa 763-8504  
Telephone : +81-877-22-4111  
Emergency telephone : CHEMTREC (24h) : +1-703-527-3887  
E-mail address : shikokumsds@shikoku.co.jp

**Recommended use of the chemical and restrictions on use**

Recommended use : Base coating

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Combustible dust

Eye irritation : Category 2A  
Carcinogenicity (Inhalation) : Category 1A  
Specific target organ systemic toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : May form combustible dust concentrations in air.  
H319 Causes serious eye irritation.  
H350i May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust.

---

## SKPT

Version 3.0	Revision Date: 12/04/2017	SDS Number: 290166-00005	Date of last issue: 10/24/2016 Date of first issue: 10/07/2015
----------------	------------------------------	-----------------------------	---

---

P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Contact with dust can cause mechanical irritation or drying of the skin.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Quartz	14808-60-7	41.67
Aluminium silicate	12141-46-7	20.84
Silicon dioxide	7631-86-9	15.42
Calcium carbonate	471-34-1	5.21
Aluminum oxide	1344-28-1	2.71
Aluminium sulphate	10043-01-3	1.49

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
 Get medical attention.

In case of skin contact : Wash with water and soap.  
 Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
 If easy to do, remove contact lens, if worn.

## SKPT

Version 3.0	Revision Date: 12/04/2017	SDS Number: 290166-00005	Date of last issue: 10/24/2016 Date of first issue: 10/07/2015
----------------	------------------------------	-----------------------------	---

---

- Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Contact with dust can cause mechanical irritation or drying of the skin.  
Causes serious eye irritation.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Silicon oxides  
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).  
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.  
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
- Local/Total ventilation : Use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe dust.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Minimize dust generation and accumulation.  
Keep container closed when not in use.  
Keep away from heat and sources of ignition.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Organic peroxides  
Explosives  
Gases

## SKPT

Version 3.0      Revision Date: 12/04/2017      SDS Number: 290166-00005      Date of last issue: 10/24/2016  
Date of first issue: 10/07/2015

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz	14808-60-7	TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
Aluminium silicate	12141-46-7	TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Aluminum oxide	1344-28-1	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
Aluminium sulphate	10043-01-3	TWA	2 mg/m <sup>3</sup> (Aluminum)	NIOSH REL

**Engineering measures** : Minimize workplace exposure concentrations.  
Apply measures to prevent dust explosions.  
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

## SKPT

Version 3.0	Revision Date: 12/04/2017	SDS Number: 290166-00005	Date of last issue: 10/24/2016 Date of first issue: 10/07/2015
----------------	------------------------------	-----------------------------	---

Use with local exhaust ventilation.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

## Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	powder
Color	:	No data available
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Dust can form an explosive mixture in air.  
Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Ingredients:****Quartz:**

Acute oral toxicity : LD50 (Rat): > 22,500 mg/kg

**Aluminium silicate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 50 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Silicon dioxide:**



## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Calcium carbonate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**Aluminum oxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Aluminium sulphate:**

Acute oral toxicity : LD50 (Rat): > 2,000 - < 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

## SKPT

Version 3.0	Revision Date: 12/04/2017	SDS Number: 290166-00005	Date of last issue: 10/24/2016 Date of first issue: 10/07/2015
----------------	------------------------------	-----------------------------	---

---

**Ingredients:****Quartz:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
Remarks: Based on data from similar materials

**Aluminium silicate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
Remarks: Based on data from similar materials

**Silicon dioxide:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**Calcium carbonate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**Aluminum oxide:**

Species: Rabbit  
Result: No skin irritation

**Aluminium sulphate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Ingredients:****Quartz:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
Remarks: Based on data from similar materials

**Aluminium silicate:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
Remarks: Based on data from similar materials

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

**Silicon dioxide:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405

**Calcium carbonate:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405

**Aluminum oxide:**

Species: Rabbit  
Result: No eye irritation

**Aluminium sulphate:**

Species: Rabbit  
Result: Irreversible effects on the eye  
Method: OECD Test Guideline 405

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Aluminium silicate:**

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: negative  
Remarks: Based on data from similar materials

**Calcium carbonate:**

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: negative

**Aluminum oxide:**

Test Type: Maximization Test  
Routes of exposure: Skin contact  
Species: Guinea pig  
Result: negative

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

**Aluminium sulphate:**

Test Type: Local lymph node assay (LLNA)  
 Routes of exposure: Skin contact  
 Species: Mouse  
 Method: OECD Test Guideline 429  
 Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Aluminium silicate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative  
 Remarks: Based on data from similar materials

**Silicon dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
 cytogenetic test, chromosomal analysis)  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Calcium carbonate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

**Aluminum oxide:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
 Method: OECD Test Guideline 476  
 Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
 cytogenetic test, chromosomal analysis)  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 475  
 Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo  
 cytogenetic assay)  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 474  
 Result: negative

## SKPT

Version 3.0	Revision Date: 12/04/2017	SDS Number: 290166-00005	Date of last issue: 10/24/2016 Date of first issue: 10/07/2015
----------------	------------------------------	-----------------------------	---

---

Remarks: Based on data from similar materials

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**Aluminium sulphate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

May cause cancer by inhalation.

**Ingredients:****Quartz:**

Species: Humans  
Application Route: inhalation (dust/mist/fume)  
Result: positive  
Remarks: IARC: (International Agency for Research on Cancer)

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**Silicon dioxide:**

Species: Rat  
Application Route: Ingestion  
Exposure time: 103 weeks  
Result: negative

**Aluminum oxide:**

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 86 weeks  
Result: negative

**IARC**

Group 1: Carcinogenic to humans

Quartz 14808-60-7

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Known to be human carcinogen

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

Quartz

14808-60-7

**Reproductive toxicity**

Not classified based on available information.

**Ingredients:****Aluminium silicate:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative  
 Remarks: Based on data from similar materials

**Silicon dioxide:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Calcium carbonate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 414  
 Result: negative

**Aluminum oxide:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Aluminium sulphate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test

## SKPT

Version 3.0	Revision Date: 12/04/2017	SDS Number: 290166-00005	Date of last issue: 10/24/2016 Date of first issue: 10/07/2015
----------------	------------------------------	-----------------------------	---

---

Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**Ingredients:****Quartz:**

Routes of exposure: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Aluminium sulphate:**

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Repeated dose toxicity****Ingredients:****Quartz:**

Species: Humans

LOAEL: 0.053 mg/m<sup>3</sup>

Application Route: Inhalation

**Aluminium silicate:**

Species: Rat

NOAEL: >= 1,000 mg/kg

Application Route: Ingestion

Exposure time: 28 Days

Remarks: Based on data from similar materials

**Silicon dioxide:**

Species: Rat

NOAEL: 1.3 mg/m<sup>3</sup>

Application Route: inhalation (dust/mist/fume)

## SKPT

Version 3.0      Revision Date: 12/04/2017      SDS Number: 290166-00005      Date of last issue: 10/24/2016  
Date of first issue: 10/07/2015

---

Exposure time: 13 Weeks

**Calcium carbonate:**

Species: Rat  
NOAEL: 1,000 mg/kg  
Application Route: Ingestion  
Exposure time: 28 Days  
Method: OECD Test Guideline 422

**Aluminum oxide:**

Species: Dog  
Application Route: Ingestion  
Exposure time: 90 Days  
Symptoms: No adverse effects.

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 90 Days  
Symptoms: No adverse effects.

**Aluminium sulphate:**

Species: Rat  
NOAEL: 18 mg/kg  
LOAEL: 90 mg/kg  
Application Route: Ingestion  
Exposure time: 28 - 53 Days  
Method: OECD Test Guideline 422  
Remarks: Based on data from similar materials

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Quartz:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 508 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 731 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Remarks: Based on data from similar materials

**Aluminium silicate:**

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202



## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 1,000 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209  
 Remarks: Based on data from similar materials

**Silicon dioxide:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
 Exposure time: 24 h  
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

**Calcium carbonate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209

**Aluminum oxide:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 218.64 mg/l  
 Exposure time: 96 h

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 7.1 mg/l  
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.89 mg/l  
Exposure time: 28 d

**Aluminium sulphate:****Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

## SKPT

Version 3.0      Revision Date: 12/04/2017      SDS Number: 290166-00005      Date of last issue: 10/24/2016  
Date of first issue: 10/07/2015

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methyl 1H-benzoimidazol-2-ylcarbamate	10605-21-7	10	*
Aluminium sulphate	10043-01-3	5000	*
Disodium hydrogenorthophosphate	7558-79-4	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Combustible dust  
Serious eye damage or eye irritation  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**US State Regulations****Pennsylvania Right To Know**

Quartz	14808-60-7
Aluminium silicate	12141-46-7
Silicon dioxide	7631-86-9
Calcium carbonate	471-34-1
Vinylacetate copolymer with ethene	24937-78-8
Other non-hazardous component	Not Assigned
Aluminum oxide	1344-28-1
Aluminium sulphate	10043-01-3
Disodium hydrogenorthophosphate	7558-79-4

**California Prop. 65****WARNING**

This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SKPT**

Version 3.0      Revision Date: 12/04/2017      SDS Number: 290166-00005      Date of last issue: 10/24/2016  
 Date of first issue: 10/07/2015

**California List of Hazardous Substances**

Silicon dioxide	7631-86-9
Aluminum oxide	1344-28-1
Aluminium sulphate	10043-01-3

**California Permissible Exposure Limits for Chemical Contaminants**

Quartz	14808-60-7
Silicon dioxide	7631-86-9
Calcium carbonate	471-34-1
Aluminum oxide	1344-28-1
Aluminium sulphate	10043-01-3


**California Regulated Carcinogens**

Quartz	14808-60-7
--------	------------

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA:**



**HMIS® IV:**

<b>HEALTH</b>	*	<b>3</b>
<b>FLAMMABILITY</b>	<b>3</b>	
<b>PHYSICAL HAZARD</b>	<b>0</b>	

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-

## SKPT

Version	Revision Date:	SDS Number:	Date of last issue: 10/24/2016
3.0	12/04/2017	290166-00005	Date of first issue: 10/07/2015

---

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/04/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8