Material Safety Data Sheet





Printed: 08/14/2015 Revision: 08/14/2015 Supersedes Revision: 07/28/2015

1. Product and Company Identification

Product Name: Satori Lifestyle Finish Part A

Trade Name: Satori Lifestyle Finish Part A

Supplier Information

Company Name: Shikoku International Corporation

301 N. Ramapart St., Suite C

Orange, CA 92868

Phone Number: +1 (978)978-0347

Emergency Contact: Chemtrec (USA) (800)424-9300

Alternate Emergency Contact: Chemtrec (International) +1 (703)527-3887

Intended Use: Industrial Wall coatings.

2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Serious Eye Damage/Eye Irritation, Category	none	Warning	Causes eye irritation
2B			
Skin Corrosion/Irritation, Category 3	none	Warning	Causes mild skin irritation

GHS Hazard Phrases

H320 - Causes eye irritation.

H316 - Causes mild skin irritation.

H335 - May cause respiratory irritation.

H303 - May be harmful if swallowed.

GHS Precaution Phrases

P103 - Read label before use. P281 - Use personal protective equipment as required.

P262 - Do not get in eyes, on skin, or on clothing. P261 - Avoid breathing mist/vapors/spray.

GHS Response Phrases

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313 - If eye irritation persists, get medical advice/attention.

P302+352 - IF ON SKIN: Wash with plenty of soap and water. P332+313 - If skin irritation occurs, get medical advice/attention.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314 - Get medical attention/advice if you feel unwell.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P313 - Get medical advice/attention.

GHS Storage and Disposal Phrases

P404 - Store in a closed container.

P402 - Store in a dry place.

P401 - Store at 45-80 degrees Fahrenheit.

Potential Health Effects (Acute and Chronic)

May cause eye irritation. May cause skin irritation. May cause respiratory irritation.

Material Safety Data Sheet



Inhalation

May cause respiratory irritation.

Skin Contact

May cause skin irritation.

Eye Contact

May cause eye irritation.

Ingestion

May be harmful if swallowed.

Medical Conditions Generally Aggravated By Exposure

Skin disorders, Respiratory disorders, Eye disorders, Skin Allergies.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)1. Ethylene glycol monopropyl ether

CAS # Concentration

2807-30-9 <3.0 %

4. First Aid Measures

Emergency and First Aid Procedures

In Case of Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If experiencing respiratory symptoms: Get medical attention immediately.

In Case of Skin Contact

In case of contact, immediately wash skin with soap and copious amounts of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists.

In Case of Eye Contact

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

In Case of Ingestion

If swallowed, wash out mouth with water provided person is conscious. Call a physician immediately. For further assistance, contact your local Poison Control Center.

Signs and Symptoms Of Exposure

Mild irritation effect.

5. Fire Fighting Measures

Flash Pt: NA Method Used: Not Applicable Explosive Limits: LEL: NE UEL: NE

Autoignition Pt: No data available.

Fire Fighting Instructions

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Use water spray to cool unopened containers.

Flammable Properties and Hazards

Product will not support combustion as supplied. Product is not considered a fire hazard. Closed containers may rupture (due to build up in pressure) when exposed to extreme heat.

Hazardous Combustion Products

In a fire, product may produce the following: Carbon monoxide, Carbon dioxide.

Suitable Extinguishing Media

Will not support combustion.